

BP SERIES

High Efficiency Chargers

100 Bank Charging Station, with Stand Included.

10 banks of 10 Chargers, each with charge status indication.

Each 10 bank is AC circuit protected with 15 Amp resettable thermal breaker with AC Lamp indication.

Charging Bay is cooled by a fan from below.

Introducing The 2020 BP100 for PBSC High Efficiency Industrial Battery Charging Bank



New! Global input Voltages, 208VAC to 264VAC
50Hz and 60 Hz.

Configured with PBSC
PBS01-002019-03
Battery Charger
FBHP00009P02
HP0180WL3, 36V/4A, NTC

And

PBS01-002029-02
Battery LI-ION 36V 13.8AH
496WH

Technical Data:

AC INPUT: 208VAC – 264VAC, 50-60 Hz, 12.5A-10A Per 10 Bank Station.

DC OUTPUT: CONSTANT VOLTAGE 36VDC 4 AMPS DC Per Charger

DIMENSIONS: WIDTH- 863MM (34"), HEIGHT-1778MM (70") DEPTH-762MM (30")

MOUNTING PATTERN: Floor Mounted on Stand

WEIGHT: 228KG. (502 lbs.) INDOOR DRY LOCATION USE.

ESA Field Approvals for use in
Canada. Additional Approvals
may be required.