



**Hard Wired**  
**Reliability**

## CHOOSING YOUR VULCAN SCA CHARGER

SCA MODEL	METER TYPE	VOLTS DC	AMPS DC	C282 SPEC RECOMMENDED	VOLTS AC	AMPS AC	CABINET	X
<b>12 VOLT CHARGERS</b>								
SCA 12/6	NDD	12	6	(QTY)	120	2	COMPACT / STANDARD	
SCA 12/10	NDD	12	10	(1) GROUP 24	120	3	COMPACT / STANDARD	
SCA 12/20	NDD	12	20	(1) GROUP 27 & 31 (1) 4D, (1) 8D	120	4	STANDARD WALL MOUNT	
SCA 12/30	NDD	12	30	(2) 8D	120	8	STANDARD WALL MOUNT	
<b>SCA 12/50</b>	NDD	<b>12</b>	<b>50</b>	<b>(3) 8D</b>	<b>120</b>	<b>9</b>	<b>FLOOR MOUNT</b>	
<b>24 VOLT CHARGERS</b>								
SCA 24/6	NDD	24	6		120	3	COMPACT / STANDARD	
SCA 24/10	NDD	24	10	(1) GROUP 24	120	4	COMPACT / STANDARD	
SCA 24/15	NDD	24	15	(1) GROUP 27 & 31	120	8	STANDARD WALL MOUNT	
SCA 24/20	NDD	24	20	(2) 4D, (2) 8D	120	10	STANDARD WALL MOUNT	
SCA 24/30	NDD	24	30	(4) 8D	120	13	STANDARD WALL MOUNT	
<b>SCA 24/50</b>	NDD	<b>24</b>	<b>50</b>	<b>(6) 8D, (3) 8V 450Ah LOCOMOTIVE</b>	<b>240</b>	<b>9</b>	<b>FLOOR MOUNT</b>	
<b>SCA 24/75</b>	NDD	<b>24</b>	<b>75</b>	<b>(3) 8V 655Ah LOCOMOTIVE</b>	<b>240</b>	<b>15</b>	<b>FLOOR MOUNT</b>	
<b>36 VOLT CHARGERS (CAN BE SET TO 32 VOLTS)</b>								
SCA 36/6	NDD	36	6		120	5	STANDARD WALL MOUNT	
SCA 36/10	NDD	36	10		120	6	STANDARD WALL MOUNT	
SCA 36/20	NDD	36	20		120	11	STANDARD WALL MOUNT	
<b>48 VOLT CHARGERS</b>								
SCA 48/10	DA DV	48	10		120	8	STANDARD WALL MOUNT	
SCA 48/20	DA DV	48	20		240	8.5	STANDARD WALL MOUNT	
<b>120 VOLT CHARGERS</b>								
SCA 120/6	2%	120	6		120	12.5	STANDARD WALL MOUNT	
SCA 120/10	2%	120	10		240	8	FLOOR MOUNT	
SCA 120/20	2%	120	20		240	18	FLOOR MOUNT	
SCA 120/30	2%	120	30		240	27	FLOOR MOUNT	

### Optional Features

	DESCRIPTION	IDENTIFIER
PACKAGE #1	<b>ANY ONE ALARM</b> (LOW VOLTAGE WITH TIME DELAY, HIGH VOLTAGE, AC FAIL, NO CHARGE) LED AND FORM "C" CONTACT	<b>CIRCLE ONE OF LVTD, HV, AC, NC</b>
PACKAGE #2	<b>ANY TWO ALARMS</b> (LOW VOLTAGE WITH TIME DELAY, HIGH VOLTAGE, AC FAIL, NO CHARGE) LED AND FORM "C" CONTACT	<b>CIRCLE TWO OF LVTD, HV, AC, NC</b>
PACKAGE #3	<b>ANY THREE ALARMS</b> (LOW VOLTAGE WITH TIME DELAY, HIGH VOLTAGE, AC FAIL, NO CHARGE) LED AND FORM "C" CONTACT	<b>CIRCLE THREE OF LVTD, HV, AC, NC</b>
PACKAGE #4	<b>ALL FOUR ALARMS</b> (LOW VOLTAGE WITH TIME DELAY, HIGH VOLTAGE, AC FAIL, NO CHARGE) LED AND FORM "C" CONTACT	<b>LVTD, HV, AC, NC</b>
FEATURE #1	<b>30 DAY, 6 HOUR AUTOMATIC EQUALIZE TIMER</b>	<b>N30D6</b>
FEATURE #5	<b>TOP MOUNTED DRIP SHIELD</b>	<b>DS</b>
FEATURE #6	<b>CUSTOM COLOUR</b>	<b>CC</b>
FEATURE #8	<b>50Hz Transformer</b>	<b>50Hz</b>
FEATURE #9	<b>240 VAC INPUT (WHERE NOT STD.)</b>	<b>240 VAC</b>
FEATURE #10	<b>ENVIRONMENT PACKAGE (CONFORMAL COATING)</b>	<b>EP</b>

Vulcan Electric Inc. 205B Konrad Cres, Markham, Ontario, L3R 8T9 Phone 905-513-1550, Fax 905-513-1557 www.chargers.ca

DIRECT SALES: sales@chargers.ca