



Product Information Sheet

SCA Standby Chargers

MODEL	CELLS	VDC	ADC	VAC	AAC	DESCRIPTIONS	Ship Wt LBS / KG	Ship Dimensions LXWXH
SCA 12/6	6	12	6	120	2	STD. CAB.; COMPACT CAB. (CC) AVAIL.	34 / 16	20X16X10"
SCA 12/10	6	12	10	120	3	STD. CAB.; COMPACT CAB. (CC) AVAIL.	35 / 16	20X16X10"
SCA 12/20	6	12	20	120	4	STANDARD CABINET	38 / 18	20X16X10"
SCA 12/30	6	12	30	120	8	STANDARD CABINET	42 / 20	20X16X10"
SCA 12/50	6	12	50	120	9	LARGE BASE MOUNT CABINET	48 / 22	28X17X28"
SCA 12/75	6	12	75	240	7	LARGE BASE MOUNT CABINET	98 / 45	28X17X28"
SCA 24/6	12	24	6	120	3	STD. CAB.; COMPACT CAB. (CC) AVAIL.	38 / 18	20X16X10"
SCA 24/10	12	24	10	120	4	STD. CAB.; COMPACT CAB. (CC) AVAIL.	40 / 19	20X16X10"
SCA 24/15	12	24	15	120	8	STANDARD CABINET	42 / 20	20X16X10"
SCA 24/20	12	24	20	120	10	STANDARD CABINET	46 / 21	20X16X10"
SCA 24/30	12	24	30	120	13	STANDARD CABINET	47 / 22	20X16X10"
SCA 24/50	12	24	50	240	9	LARGE BASE MOUNT CABINET	110 / 50	28X17X28"
SCA 24/75	12	24	75	240	15	LARGE BASE MOUNT CABINET	125 / 57	28X17X28"
SCA 24/100	12	24	100	240	20	LARGE BASE MOUNT CABINET	150 / 69	28X17X28"
SCA 36/6	18	36	6	120	5	STANDARD CABINET	58 / 27	20X16X10"
SCA 36/10	18	36	10	120	6	STANDARD CABINET	62 / 29	20X16X10"
SCA 36/20	18	36	20	120	11	STANDARD CABINET	72 / 33	20X16X10"
SCA 36/50	18	36	50	240	14	LARGE BASE MOUNT CABINET	106 / 49	28X17X28"
SCA 48/10	24	48	10	120	8	STANDARD CABINET	62 / 29	20X16X10"
SCA 48/20	24	48	20	240	8.5	STANDARD CABINET	64 / 30	20X16X10"
SCA 120/6	60	120	6	120	12.5	STANDARD CABINET	64 / 30	20X16X10"
SCA 120/10	60	120	10	240	8	STANDARD CABINET	96 / 44	20X16X10"
SCA 120/20	60	120	20	240	18	LARGE BASE MOUNT CABINET	112 / 51	28X17X28"
SCA 120/30	60	120	30	240	27	LARGE BASE MOUNT CABINET	160 / 73	28X17X28"
PACKAGE #1	ANY ONE ALARM					(LOW VOLTAGE, HIGH VOLTAGE, AC FAIL, NO CHARGE) LED AND FORM "C" CONTACT		
PACKAGE #2	ANY TWO ALARMS					(LOW VOLTAGE, HIGH VOLTAGE, AC FAIL, NO CHARGE) LED AND FORM "C" CONTACT		
PACKAGE #3	ANY THREE ALARMS					(LOW VOLTAGE, HIGH VOLTAGE, AC FAIL, NO CHARGE) LED AND FORM "C" CONTACT		
PACKAGE #4	ALL FOUR ALARMS					(LOW VOLTAGE, HIGH VOLTAGE, AC FAIL, NO CHARGE) LED AND FORM "C" CONTACT		
FEATURE #1						30 DAY 6 HOUR AUTOMATIC EQUALIZE TIMER		
FEATURE #2						4 ALARM TEST FUNCTION		
FEATURE #3						GROUND FAULT ALARM – NEGATIVE OR POSITIVE		
FEATURE #4						UPGRADE TO DIGITAL AMMETER AND VOLTMETER		
FEATURE #5						TOP MOUNTED DRIP SHIELD		
FEATURE #6						Custom Color, International Orange		
FEATURE #7						KIT FORM CHARGERS (SUFFIX BCT1)		
FEATURE #8						50 CYCLE MODELS		
FEATURE #9						240 V INPUT (WHERE NOT STANDARD)		