

SM SERIES

High Efficiency Chargers

DIRECT REPLACEMENT

Direct Replacement
for the current Model

EA 12/10BT2

CANADA POST
CONFIGURATION

New Slim Cabinet
Design Made with
18ga. Satin Coated
Galvanized Steel
Powder Coated and
Includes Integrated
Cable wrap Bracket.

Heavy Duty AC Cord

1 YEAR Warranty
Full Replacement
Warranty!

Introducing The 2019 SM12/10BT2

CANADA POST CONFIGURATION

High Efficiency 12 Volt 10 Amp Industrial Battery Charger

New! Global input Voltages,
100VAC to 264VAC
50Hz and 60 Hz.

High Efficiency Rugged
Switch Mode design
customized to suit your
needs for lead Acid, AGM
and Gel type batteries.

12 VDC 10 Amp output with
Current Limiting, Constant
Voltage and Float voltage.

Reliability and toughness,
Minimum Design Mean time
to Failure of 30,000 hours in
full rated load operation at
25C and Operating
Temperatures of
-29C to 45C.

AC and DC inline fuses with
short circuit protection.
(Reverse Polarity Protection
Available, ask for Details)

Level VI Efficiency



Technical Data:

AC INPUT: 100VAC – 264VAC, 50-60 Hz, 2A

DC OUTPUT: CONSTANT VOLTAGE 14.4VDC

CURRENT LIMIT 10 AMPS DC

FLOAT HOLD VOLTAGE 13.6VDC

FLOAT HOLD MAX. AMPERAGE 3ADC

MINIMUM CHARGE VOLTAGE 5VDC

DIMENSIONS: WIDTH- 6", HEIGHT-8" DEPTH- 2"

MOUNTING PATTERN: BULKHEAD MOUNT

WEIGHT: 4.7lbs. INDOOR DRY LOCATION USE.

