

SM SERIES

High Efficiency Chargers

DIRECT REPLACEMENT

Direct Replacement
for the current Model

CV24/10EA

CV24/15EA

FR24/10EA

Heavy Duty AC Cord

1 YEAR Warranty
Full Replacement
Warranty!

Introducing The 2020 SM24/13 High Efficiency 24 Volt 13 Amp Industrial Battery Charger



New! Global input Voltages,
100VAC to 264VAC
50Hz and 60 Hz.

High Efficiency Rugged
Switch Mode design
customized to suit your
needs with either River or
Discovery batteries.

24 VDC 13 Amp output with
Current Limiting, Constant
Voltage and Float voltage,
short circuit protection..

Reliability and toughness,
Minimum Design Mean time
to Failure of 30,000 hours in
full rated load operation at
25C and Operating
Temperatures of
-29C to 45C.

AC and DC inline fuses with
short circuit and reverse
polarity protection.

Technical Data:

AC INPUT: 100VAC – 264VAC, 50-60 Hz, 4.8A
DC OUTPUT: CONSTANT VOLTAGE 29.4VDC
CURRENT LIMIT 13 AMPS DC
FLOAT HOLD VOLTAGE 27.2VDC
FLOAT HOLD MAX. AMPERAGE 4ADC

DIMENSIONS: WIDTH- 4", HEIGHT-9" DEPTH-2.75"

MOUNTING PATTERN: BENCH MOUNT

WEIGHT: 4.1lbs. INDOOR DRY LOCATION USE.


C  US
5012033

Level VI Efficiency